

## urraco 111 lamborghini

The Lamborghini URRACO:
A high performance mid engined four seater "Berlinetta" with medium cubic capacity.
Successor to the advanced technical designs incorporated in the 350 and 400 GT 2+2, the URRACO offers outstanding performance and road holding, combined with all round versatility.











design

bertone





The URRACO, with its Bertone designed body, is both streamlined and compact. The many innovative features of the car include an aerodynamic body which combines comfort to complement the car's outstanding performance.











## PRINCIPLE ENGINEERING FEATURES

Suspension: McPherson four wheel independent struts, with high-precision geometry.

Steering: Rack and pinion. This has been chosen following the study of advanced technical data which has proved that this type of steering is the most suitable for sports cars. The absence of a steering column allows for the maximum degree of safety.

Engine: The V8 engine mounted at 90 degrees combines maximum power at full revs, with complete flexibility at low and medium speeds.



## **LAMBORGHINI URRACO 111**

Engine and transmission

Engine: V 8 at 90° Displacement: 2463 cm3 (86x53) Compression ratio: 10.4:1 Maximum horsepower: 180 HP (DIN) Maximum torque: 20 Mkg. Maximum RPM: 7500 Engine location: central-transverse Block and heads: Light alloy Main bearings: 5 Ignition: one distributor and 1 coil Spark plugs: Bosh 235 P 21 Fuel pump: 1 Bendix electric pump 12 V Carburation: 4 twin - choke carburettors Lubrication: gear pump Cooling System: water-cooling by means of a centrifugal pump and of 3 electric fans (two of them with a thermal contact)

Electrical system Voltage: 12 V Battery: 55 Amp Alternator: Bosch 770 W

Clutch Single dry disc

Gearbox Lamborghini 5 speeds + reverse **Transmission** 

Half-shafts with constant-moving joints

Chassis

Body: monocoque type
Front suspension: Mc Pherson
Rear suspension Mc Pherson
Both with anti-roll bars
Brakes: twin-circuit ventilated brakes

Brakes: twin-circuit ventilated brakes Steering: rack-and-pinion-type Wheels: magnesium alloy - 7,5"x14" Tyres: radial,low profile 205/70 VR 14 type

Body 4 seater coupé (Bertone)

Lenght: 4440 mm. Width: 1740 mm. Height: 1160 mm. Wheelbase: 2450 mm. Track front 1450 mm., rear 1470 mm. Trunk capacity: 285 lt.

Weight

Dry weight (with oil and water): 1300 kos.

Performance

Max speed: 140 mph. Acceleration on standing km (with 2 Passengers): 26,8"

lamborghini



AUTOMOBILI FERRUCCIO LAMBORGHINI S.p.A. 40019 S. AGATA BOLOGNESE (BO) ITALIA TEL. (051) 956171-2-3